

*Visual Sensations™*

**CRT**

21" (19.9" VIS) High Performance,  
High Contrast Picture Tube,  
Anti-Reflection & Anti-Static Coating

**MAXIMUM RESOLUTION**

1920 x 1440 @ 75Hz

**DOT PITCH**

0.22mm Horizontal Dot Pitch  
(0.25mm Dot Pitch)

**FREQUENCY**

Horizontal: 30 ~ 117KHz

Vertical: 50 ~ 160Hz

**BANDWIDTH**

230MHz

**SIGNAL CONNECTOR**

15-pin D-Sub. (Analog R,G,B)

**FEATURES**

Superb Image Quality  
On-Screen Digital Controls  
Plug & Play (VESA DDC 2B)  
PC & Mac\* Compatible  
Tilt & Swivel Base

**REGULATORY APPROVALS**

UL, G/S, FCC Class B, DHHS, MPR II  
SEMKO, NUTEK, CE, EPA, TCO 95,  
ISO 9001, ISO 14001

**POWER SUPPLY**

100-240 VAC, 50/60 Hz,  
Auto Switching

**MONITOR DIMENSIONS**

19.9"(W) x 20.9"(D) x 19.1"(H)  
506mm(W) x 527mm(D) x 485mm(H)

**BOX DIMENSIONS**

24.6"(W) x 22.5"(D) x 22.6"(H)  
625mm(W) x 572mm(D) x 574mm(H)

**WEIGHT**

Net: 63.4 lbs. / 28.8 Kg.  
Gross: 73.7 lbs. / 33.5 Kg.

**WARRANTY**

3 Year Limited Parts & Labor  
KDS Advanced Replacement Express Service

21" High Performance Monitor

# VS-21e

**21" High Performance Monitor**



The **VS-21e** is designed for imaging and CAD/CAM/CAE professionals who want maximum performance from today's technology. A powerful tool for high-end graphics, production, scientific and engineering design applications, its advanced features deliver sharp pictures, crisp colors and precise lines with virtually no eyestrain.



[www.kdsusa.com](http://www.kdsusa.com)

**KDS**

©2002 KDS USA Inc. All rights reserved. Specifications, design, availability and warranty subject to change without notice. This document is used for reference only. KDS USA is not responsible for any errors. \*Mac adapters may be required.